

Province of British Columbia
Ministry of Environment
Inventory and Engineering Branch

CONSTRUCTION OF OBSERVATION WELL WR-261-80

WILLIAMS LAKE AREA

CONTRACT NO. 70

W.S. Hodge
Technician
Groundwater
Hydrology Section

Victoria, B.C.
Feb. 1981

TABLE OF CONTENTS

	<u>Page</u>
Table of Contents	ii
List of Figures	iii
List of Appendices	iii
1. Introduction	1
2. Well Construction and Testing	1
3. Geology	3
4. Hydrogeology	4
5. Water Quality	6
6. Conclusions	7
7. References	9

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Well Location Plan	10
2	Site Plan	11
3	Well Design and Geology	12
4	Bedrock Geology	13

LIST OF APPENDICES

Appendix A	Well Log, Contract Costs, Pump Tests Data, Water Level Recorder Installation Specifications, Application Form
Appendix B	Water Quality Lab Reports, Schoeller Plots, Water Level Recorder Graphs showing earthquake response

CONSTRUCTION OF OBSERVATION WELL WR 261-80

WILLIAMS LAKE AREA

Contract No. 70

1. INTRODUCTION

One 203 mm diameter observation well was drilled and completed to a depth of 79.2 metres (260 feet) off Dog Creek Road south of Williams Lake (Figure 1). The well was drilled by Manville Drillers of Williams Lake and tested by Ken Branscombe of Hillside Pumps, Williams Lake in September 1980. Total contract costs for well construction and testing were \$8,092.00.

The area around Dog Creek Road was chosen as a high priority area for establishment of an observation well on the recommendations of Choy (1978). Groundwater exploration in this area had been previously recommended by our Ministry (Hodge, 1976) in a report to the Land Management Branch at Williams Lake.

As shown in Figure 1 well density along Dog Creek Road is very high with residents relying entirely on the local groundwater reserves. Figure 2 shows the well location in greater detail.

Construction of an observation well was required to monitor water level fluctuation and long term effects of groundwater extraction in the area. An automatic water level recorder and protective housing were installed on the well head. This equipment should remain in place for a minimum of 5 years.

2. WELL CONSTRUCTION AND TESTING

Drilling was carried out to a depth of 79.2 metres using an air rotary drill rig (Speedstar) with casing hammer. To allow for surface grouting, a 4.9 metre length of temporary casing was installed. This

casing was later removed and the annular space around the 203 mm diameter casing was grouted. This 203 mm casing extends from ground surface to a depth of 61 metres through unconsolidated material comprised of brown and blue clay with gravel (Figure 3). A drilling foam was pumped into the hole while drilling through both the overburden and bedrock. The foam was used as a precaution against unstable or caving conditions. At times drilling 12.2 metres open hole ahead of the casing was possible in overburden. Although foam aided in keeping the hole open, materials were quite firm.

The major source of water is derived from bedrock. This source is likely supplemented from the water-bearing gravels above. Examination of the drill returns revealed the bedrock to be a highly fractured tertiary sandstone. Drilling action showed the sandstone to be firm but grading from soft to hard. The soft layering encountered appears to be compacted sand between layers of lithified bedrock.

The well was developed by surging and pumping with compressed air for a period of 1.5 hours. The water had cleared in this time and was visibly sand free.

The well was pumped with a 5 h.p. - 13 stage Jacuzzi submersible pump. The first test on September 3rd was terminated after only 70 minutes of pumping because of a pump failure. The second test on September 5th was completed without interruption and the well was pumped at a rate of between 4.13 litres/second and 4.54 litres/second (65.4 and 72 USgpm for a period of 560 minutes (9.3 hours). The pump intake was set at 42.7 metres below the top of the well casing during this test and the static water level was 25.5 metres. Test data is shown in Appendix A. A drawdown of 0.83 metres occurred over the test period representing approximately 5 percent of the total available drawdown. Using these figures and assuming stabilization of the pumping water level occurred during the test, a maximum specific capacity of 5.47 litres/second/metre of drawdown (26.5 USgpm/ft. of drawdown) can be calculated. If the lower

pumping rate of 4.13 litres/second is used, a specific capacity of 4.92 litres/second/metre of drawdown is derived. This figure may be more realistic considering stabilization did not occur when the well was pumped at the higher rate of 4.5 litres/second (72 USgpm). On the basis of these calculations the well should theoretically be capable of sustaining a yield of 101 litres/second or 1600 USgpm if the pump were lowered to 61 metres, and the maximum available drawdown (at the time of testing) were utilized.

A long term pump test of minimum duration of 72 hours at higher pumping rates would have to be conducted in order to define more clearly the full capabilities of this well.

Water level recovery was rapid. The initial recovery reading 30 seconds after the pump was stopped was recorded as 0.13 metres (0.43 feet) above the original static water level. This excellent recovery response was due in part to the well construction (i.e. the well was completed open hole in the bedrock and thus no restrictions such as slotted casing were present). This response also indicates the aquifer is subject to recharge. A water level of 0.02 metres (0.07 feet) below the original static water level was recorded within one hour of stopping the pump. An automatic water level recorder was installed on the well head at this point and the remaining recovery was recorded.

3. GEOLOGY

Surficial and bedrock geology in the Williams Lake area has been mapped by Tipper (1959). Bedrock geology has been shown in Figure 4 of the text.

The glacial history in the Williams Lake valley is complex and involved at least two periods of glaciation. Each advance appears to have occurred in a westerly direction towards the Fraser River. According to Callan (1968) the first advance was more pronounced than the last, eroding

the Williams Lake valley to at least an elevation of 1450 feet and depositing a thick sequence of sands, silts and gravels as it receded. The second advance was less severe and did not erode the valley below an elevation of 1800 feet.

Large meltwater or outwash channels of recent alluvium materials cover most of the Williams Lake valley and Chimney Creek areas with some pitted terrain to the north of Williams Lake. The alluvium consists of mainly till, sand, gravel and silt.

The study area is primarily underlain by a thin drift cover overlying bedrock. Geological logs of wells drilled within the immediate study area indicate bedrock varies between surface and 76 metres. The bedrock geology map shown in Figure 3 indicates surficial deposits of till, gravel, sand, clay and silt bounded by tertiary volcanic bedrock to the east and west (Figure 3). Surficial deposits were found to be 58.5 metres thick (192 feet) at the observation well drill site.

Recent hydrographs obtained from the monitoring of this observation well have shown water level movement in the well caused by earthquakes (Appendix B). A spike, 0.038 metres in length appeared at approximately 9:00 a.m., December 17th on the hydrograph shown in Appendix B. This spike was caused from the December 17th earthquake (9:20 a.m.) which originated approximately 200 kilometres west of Estevan Point on Vancouver Island.

Another spike, 0.072 metres in length occurred November 8th and this is believed to be caused from the southern Italy earthquake.

4. HYDROGEOLOGY

The Groundwater section has approximately 180 records of wells drilled along Dog Creek Road (Figure 1). The Dog Creek Road area was reviewed as part of a groundwater study done in July 1976. At that

time the average depth of wells drilled along Dog Creek Road was determined at 31.4 metres (103 feet). Well depths ranged from shallow dug wells and drilled wells up to 94.5 metres (310 feet). Wells drilled recently are generally deeper than 31.4 metres. Through discussions with local residents and comparisons of dated and recent water levels in the area it is apparent that water levels may be declining. This may be due to the numerous wells being constructed in this area causing an ever increasing demand on the groundwater resource.

Until the construction of the observation well, the greatest recorded yield on Dog Creek Road was the Kendall Acres Mobile Home Park well (Figure 1). This well is 27 metres deep (88 feet) and reports a specific capacity of 3.0 litres/second/metre of drawdown (19.2 USgpm/ft.). The recommended pumping rate of this well was set conservatively at 50 USgpm by the driller. The majority of wells along Dog Creek Road are, however, capable of yielding 0.06 to 0.25 litres/second (1 to 4 USgpm). The major aquifer throughout the Dog Creek Road area appears to be a tertiary sandstone. Groundwater recharge to this area is likely supplied from higher elevations to the south. Groundwater discharge has been noted downslope near Shaw Auto by local residents. As mentioned in the 1976 report, glaciofluvial deposits surround Bond Lake. These deposits are free draining possibly supplying recharge to areas downslope to the north (observation well site).

Bond Lake is located on a knoll approximately 76 metres higher in elevation than the drill site and is located 1200 metres southwest of the drill site. Aerial photographs indicate Bond Lake could be a contributing source of recharge to this aquifer.

5. WATER QUALITY

Water samples were collected and submitted for complete chemical analysis at the beginning and the completion of the pump test. The

analyses indicate the groundwater is hard (547 and 567 mg/l) with corresponding pH values of 8.0, and moderately mineralized (T.D.S. 696 and 700 mg/l). These results indicate the presence of primarily a calcium-magnesium bicarbonate type groundwater. The total iron content recorded at the start of pumping was 1.3 mg/l. After 7 hours of pumping the dissolved iron content was reduced substantially and recorded as 0.1 mg/l. No iron was recorded in suspension at the end of pumping.

Although below the recommended standard of 10 mg/l, nitrite and nitrate levels are quite high (6.6 mg/l). Levels as high as this could be an indication that the groundwater is receiving some organic constituents somewhere along its flow path. Hydrograph records have shown this aquifer is responsive to the effects of local pumping and earthquakes indicating the aquifer has a high transmissivity and good permeability. Although desirable in any aquifer these features also make an aquifer susceptible for movement of pollutants. It should be noted, however, that although a nitrite and nitrate level of 6.6 mg/ is above the normal amounts of these elements found in groundwater, these levels are still below the recommended standard and may be of little concern.

A water sample was also collected from the Kendall Acres Mobile Home Park located approximately 250 metres east of the observation well. This sample was submitted for complete chemical analysis. The analyses results for this well and the observation well were plotted using the Schoeller method (Appendix B) and the groundwaters were found to be different types and probably not of the same flow system. The Kendall Acres well is (26.8 metres) deep and the major water bearing zone is located between 11 metres and 25.3 metres. The water quality of this well is considerably lower in hardness (218 mg/l) and less mineralized (484 mg/l) than the water sampled at the observation well site.

6. CONCLUSIONS AND RECOMMENDATIONS

- The aquifer encountered is a fractured rock, probably tertiary sandstone.
- Recharge to this aquifer likely occurs in the south. Geologic mapping and aerial photography indicate that Bond Lake may be hydraulically connected to this aquifer.
- This aquifer appears to have the potential for supporting a high capacity well or wells. The pump test data has indicated a properly designed and constructed well within this aquifer could theoretically sustain a yield of several hundred gallons per minute.
- A further long term pump test of a minimum duration of 72 hours is necessary, however, before any definite or final conclusions can be made regarding the capabilities or characteristics of this aquifer. Although recovery data suggests this aquifer is extensive, long term pumping could reveal hydraulic boundaries not evident from short duration tests. Long term, high rate pumping tests are not within the scope of the observation well establishment program under which the well was constructed.
- Development of this aquifer may now be an important consideration when concerned with the long term planning of areas along Dog Creek Road. The option of pumping water to this area from Williams Lake could be dismissed pending further testing of this aquifer.
- Water quality is acceptable and meets the standards set by the Canadian Drinking Water Quality Guidelines for all parameters tested. Nitrogen with respect to nitrite and nitrate was high, but below the recommended standard.
- This well should be sampled for complete chemical analysis at least

twice during its monitoring period - once during the late summer months when water levels are historically at their lowest and once during the spring. Testing for iron and nitrogen levels should be of particular importance.

W. S. Hodge

W.S. Hodge
Technician
Groundwater
Hydrology Section

WSH/dma

APPENDIX "A"

Well Log, Contract Costs, Pump Test Data,
Water Level Recorder Installation Specifications,
Application Form


Williams Lake Observation Well #261

(Note-Fish & Wildlife shed
to the left and Dog Creek road
in the background)



Williams Lake Observation Well WR 261-80


Pump Test -- Sept. 5, 1980




5 HP Submersible pump
installed and pumping about
to begin.



Discharge of
72 USgpm.



LOCATION PLAN



SITE PLAN



Province of British Columbia
Ministry of the Environment
ENVIRONMENTAL AND ENGINEERING SERVICE
WATER INVESTIGATIONS BRANCH

TO ACCOMPANY REPORT ON
 Construction of Observation well
 WR 261-80-Williams Lake Area

SCALE: VERT. 1 cm = 205 metres

HOR.

DATE
 Oct. 1980

D.A. Lowen


ENGINEER

FILE No. DWG. No. Figure 2

PLAN SHOWS HIGH WELL DENSITY
ALONG DOG CREEK ROAD



metres below
ground surface



WELL DESIGN & GEOLOGY

Williams Lake Observation Well WR 261-80




Province of British Columbia
Ministry of the Environment
ENVIRONMENTAL AND ENGINEERING SERVICE
WATER INVESTIGATIONS BRANCH

TO ACCOMPANY REPORT ON
Construction of Observation well
WR 261-80-Williams Lake Area

SCALE: VERT. 1 cm = 4.7 metres
HOR. N/A

DATE
Oct. 1980

D.A. Lowen ENGINEER
FILE No. DWG. No. Figure 3



LEGEND

- | | |
|--|---|
| <div style="border: 1px solid black; padding: 2px; width: 30px; height: 30px; background-color: #add8e6; display: flex; align-items: center; justify-content: center; margin: 0 auto;">1</div> | CHERT ARGILLITE LIMESTONE
GREENSTONE AND CONGLOMERATE |
| <div style="border: 1px solid black; padding: 2px; width: 30px; height: 30px; background-color: #808080; display: flex; align-items: center; justify-content: center; margin: 0 auto;">4</div> | RHYOLITE ANDESITE DACITE TRACHYTE
RELATED TUFF AND BRECCIA BASALT
MINOR SEDIMENTS |
| <div style="border: 1px solid black; padding: 2px; width: 30px; height: 30px; background-color: #ffff00; display: flex; align-items: center; justify-content: center; margin: 0 auto;">7</div> | BASALT ANDESITE RELATED TUFF AND
BRECCIA MINOR CONGLOMERATE
GREYWACKE SHALE AND DIATOMITE |
| <div style="border: 1px solid black; padding: 2px; width: 30px; height: 30px; background-color: #800000; display: flex; align-items: center; justify-content: center; margin: 0 auto;">8</div> | TILL GRAVEL SAND CLAY AND SILT |

(from Tipper, 1959)



Province of British Columbia
Ministry of the Environment
ENVIRONMENTAL AND ENGINEERING SERVICE
WATER INVESTIGATIONS BRANCH

TO ACCOMPANY REPORT ON

Construction of Observation Well
WR 261-80 - Williams Lake Area

SCALE: VERT.
HOR.

DATE
Oct. 1980

D.A. Lowen

ENGINEER

FILE No.

DWG. No.

Figure 4

APPENDIX "A"

Well Log, Contract Costs, Pump Test Data,
Water Level Recorder Installation Specifications,
Application Form

OBS. WELL #261

WATER WELL RECORD

DEPT. OF ENVIRONMENT, WATER RESOURCES SERVICE, WATER INVESTIGATIONS BRANCH

VICTORIA, BRITISH COLUMBIA

LEGAL DESCRIPTION: LOT A SEC. _____ TP. _____ R. _____ D.L. 9849 LAND DISTRICT CARIBOO PLAN 0645DESCRIPTIVE LOCATION OFF DOG CREEK ROAD, S.E. OF DENNY ROAD, WILLIAMS LAKE LICENCE NO. _____ DATE _____OWNER'S NAME MINISTRY OF ENVIRONMENT ADDRESS 105 DILIGHTON VICTORIA B.C.DRILLERS NAME MANVILLE DRILLING ADDRESS WILLIAMS LAKE DATE COMPLETED SEPT 1980DEPTH 260' ELEVATION _____ ☐ ESTIMATED ☐ SURVEYED CASING DIAM. 8" LENGTH 200'METHOD OF CONSTRUCTION AIR ROTARY CASING DIAM. 8" LENGTH 200'SCREEN LOCATION _____ SCREEN ☐ SIZE _____ LENGTH _____ TYPE _____SANITARY SEAL YES ☒ NO ☐ SCREEN ☐ SIZE _____ LENGTH _____ TYPE _____PERFORATED CASING ☐ LENGTH _____ PERFORATIONS FROM _____ TO _____GRAVEL PACK ☐ LENGTH _____ DIAM. _____ SIZE GRAVEL, ETC. _____DISTANCE TO WATER 83.64' ☐ ESTIMATED WATER LEVELFROM TOP CASING ☐ MEASURED ELEVATION _____ ARTESIAN PRESSURE _____DATE OF WATER LEVEL MEASUREMENT SEPT 8/80 WATER USE OBSERVATION WELL

CHEMISTRY

TEST BY _____ DATE _____

TOTAL DISSOLVED SOLIDS _____ mg/l TEMPERATURE _____ °C PH _____ SILICA (SiO₂) _____ mg/lCONDUCTANCE _____ μ mhos/cm AT 25°C TOTAL IRON (Fe) _____ mg/l TOTAL HARDNESS (CaCO₃) _____ mg/lTOTAL ALKALINITY (CaCO₃) _____ mg/l PHEN. ALKALINITY (CaCO₃) _____ mg/l MANGANESE (Mn) _____ mg/l

COLOUR _____ ODOUR _____ TURBIDITY _____

ANIONS

mg/l

epm

CARBONATE (CO₃)BICARBONATE (HCO₃)SULPHATE (SO₄)

CHLORIDE (Cl)

NO₂ + NO₃ (NITROGEN)

• TKN. (NITROGEN)

PHOSPHORUS (P)

• TKN • TOTAL KJELDAHL NITROGEN

NO₂ • NITRITE NO₃ • NITRATE

CATIONS

mg/l

epm

CALCIUM (Ca)

MAGNESIUM (Mg)

SODIUM (Na)

POTASSIUM (K)

IRON (DISSOLVED)

CHEMISTRY SITE NO. _____

CHEMISTRY FIELD TESTS

TEST BY W. HODGE DATE SEPT 5/80 EQUIPMENT USED HACHTEMP. 7.6°CPH 7.8HARDNESS 650COND. 1000IRON .8 ± 1.1ALK 632

CONTENTS OF FOLDER

☒ DRILL LOG☐ PUMP TEST DATA☐ CHEMICAL ANALYSIS☐ SIEVE ANALYSIS☐ GEOPHYSICAL LOGS☐ REPORTOTHER LOCATION SKETCHES

SOURCES OF INFORMATION _____

Z 2 WELL NO. 14

E

N

Z 2 x 14 Y 4 NO.NAT. TOPO. SHEET NO. 1

PRODUCTION TEST SUMMARY

DATE SEPT 5/80TEST BY HILLSIDE PUMPS - WILLIAMS LAKEBAIL TEST ☐ PUMP TEST ☒ DURATION OF TEST 9:50 AMRATE 72 USGPM DRAWDOWN 2.72'WATER LEVEL AT COMPLETION OF TEST 86.36'AVAILABLE DRAWDOWN ± 100' SPECIFIC CAPACITY ± 25 USGPM/ft

PERMEABILITY _____ STORAGE COEFF. _____

TRANSMISSIVITY _____

RECOMMENDED PUMPING RATE _____

RECOMMENDED PUMP SETTING _____

LITHOLOGY

FROM	TO	DESCRIPTION
0	43	S.F.G. w/ LITTLE CLAY binder VERY SOFTY ANGULAR & SUB- ANGULAR S.F.G. GRAINS SOME ROUNDED, TILL
43	45	BROKEN ROCK LAYER OR BLDR., HARD
45	52	S.F.G. & BROKEN ROCK FRAGS., GRAY
52	64	BROWN CLAY
64	88	LITTLE CLAY BINDER, LIGHTER TAN COLOUR, TILL OR CLAY
88	176	BROKEN ROCK BLACK GRAVEL
176	178	BROWN CLAY
178	192	GRAVEL & SAND w/ SOME CLAY
192	204	DARK GREY COLORED BEDROCK SOME S.F.G. (COULD BE S.F.G. IN BEDROCK FRACTURES) SANDY GREY SHALE
204	210	SAND & CLAY, RED BROWN COLOUR PINKISH WATER
210	222	SAND & CLAY
222	223	SAND BROKEN ROCK AND WHITE CLAY SOME DIRTY SANDSTONE
223	260	FRAG. ROCK & LAYERS OF BROWN CLAY.

MANVILLE DRILLING (B.C.) CO. LTD.

R.R. 2, BOX 25, COMMODORE CRESCENT, WILLIAMS LAKE, B.C. V2G 2P2
TELEPHONES: 989-4301 - 392-7562

No 125

19 80

Sept 2

ACCOUNT WITH Ministry of Environment

ADDRESS Parliament Buildings, Victoria, B.C. V8V 1X5

2% Carrying Charge per month on overdue accounts, including interest and payment in arrears.

Re - water well construction contract no. 70

Williams Lake, B.C.

17' - 12" surface casing @ \$38.00 per ft	646 00
183' - 8" drilling casing in overburden @ \$27.00 per ft	4,941 00
8" drilling in bedrock 60 ft @ \$15.00 per ft	900 00
17' - 8" overlap casing @ \$12.00 per ft	204 00
1 - 8" drive shoe	130 00
3 hrs. developing & cementing @ \$150.00 per hr.	450 00
capping well	50 00
SUB-TOTAL	7,320 00
Mobilization & Demobilization of pump and equipment	280 00
12 hours pumping	456 00
1 hour recovery	35 00
TOTAL	8,092 00

TERMS:

Upon default of any payment the entire balance becomes due and payable and a Mechanics Lien may be filed.

In the event of non payment of the said total charge, the owner authorizes this company to take whatever legal steps may be deemed necessary to collect and agrees to pay all collection costs.

DRILLER:

L.H. Beckett

ACCEPTED BY

W.S. Hodge Sept 6/80

APPENDIX

"CONSTANT RATE" PUMPING TEST DATA FROM WELL NO. 261

Date September 12, 1980

TEST #1

[illegible]

RECOVERY READINGS IN WELL NO. 261 AFTER "CONSTANT RATE" PUMPING TEST #1

[illegible]

APPENDIX

"CONSTANT RATE" PUMPING TEST DATA FROM WELL NO. 261

Date September 11, 1980

TEST #2

Time	Time (t) since start of pumping in mins.	Depth to water in well from top of casing in feet	Drawdown in well in feet (static =83.64)	Height of water in tube on orifice pipe in inches	U.S.gals. per min. discharge from well	Pump Set @ 140' Below Tob Casing
8:25 AM	0	83.64	0			Observer-Hodge
	.5					Missed Reading
	1	85.30	1.66			
	1.5	85.30	1.66			
	2	85.30	1.66			Powers M-Scope
	2.5	85.31	1.67			Used Throughout
	3	85.31	1.67			Test
	3.5	85.31	1.67			
	4	85.33	1.69			
	4.5	85.35	1.71			
	5	85.36	1.72			
	6	85.69	2.05			
	7	85.68	2.04			
	8	85.62	1.98			
	9	85.55	1.91			
	10	85.58	1.94		65.4	
	12	85.61	1.91		(3.96 4/5)	Water Sample
	14	85.66	2.02			Collected For
	16	85.67	2.03			Complete Analysis
	18	85.67	2.03			@ 12 min into test
	20	85.68	2.04		65.4	
	25	86.22	2.58			
	30	85.82	2.18			
	35	85.86	2.22			
	40	85.87	2.23			Observer Change
	45	85.88	2.24		65.4	@ 70 min-Wilkinson
	50	85.88	2.24			
	55	85.88	2.24			Hach Test @
9:25 AM	60	85.88	2.24			11:15 AM
	70	85.87	2.23		72	Iron-.8--1.1
	80	85.84	2.20		(4.37 4/5)	Cond. - 1000
	90	85.92	2.28			PH - 7.8
	100	85.94	2.50		65.4	Hardness - 649.8
	120	85.98	2.34			Temp - 7.6
	140	86.01	2.37			Alkalinity - 632

"CONSTANT RATE" PURGING TEST DATA FROM WELL NO.

Date

Time	Time (t) since start of pumping in mins.	Depth to water in well from top of casing in feet	Drawdown in well in feet (static =)	Height of water in tube on orifice pipe in inches	U.S.gals. per min. discharge from well
	160	86.00	2.36	:	
	180	86.08	2.44		
11.45	200	86.11	2.47		
	230	86.12	2.48	65.4	
	260	86.08	2.44	(3.96 l/s)	
	290	86.13	2.49		
	320	86.18	2.54		Temp-76 °C
	350	86.21	2.57	72	Cond-1010
	380	86.22	2.58	(4.37 l/s)	*
	400*				Pump Acting Up
	410	86.33	2.69		Flow Stopped Non
	440	86.33	2.69		Pumping Level
	480	86.38	2.74	72	Returned To 83.85
	500	86.38	2.74	(4.37 l/s)	Within 1/2 min.
	540	86.36	2.72		OK after 3 min
5:45 PM	560	86.36	2.72	Pump Shut off	
Note-Water Sample Collected for complete analysis @ 500 min into test.					

سانچہ ۱۰۰

!

[illegible]

Williams Lake Observation Well
WRE-30 (Contract 70)

DRAWDOWN DATE:

$Q = 65.4$
USgpm

$$T_1 = \frac{264 \cdot Q}{\Delta s} = \frac{264 \times 65.4}{0.40} = 43,164 \text{ USgpd/ft}$$


$$T_2 = \frac{264 \cdot Q}{\Delta s} = \frac{264 \times 72}{0.50} = 38,016 \text{ USgpd/ft}$$

$Q = 72$ USgpm


$Q = 72$ USgpm

DRAWDOWN, IN FEET

Time since pumping started, in minutes



Residual Drawdown, s, in feet





Province of
British Columbia

Ministry of
Environment
and
Natural Resources

MEMORANDUM

To: D. Lowen
Geological Engineer
Groundwater
Hydrology Section

Date: September 11, 1980

File: 0183613-B-261

Re: Williams Lake (Dog Creek Road) Observation Well WR261-80, Site 1401769

Background Information:

It was recommended in 1977 that the Williams Lake area be included in the proposal for expansion of the observation well network (Choy, 1977). An attempt to locate a suitable abandoned drilled well along Dog Creek Road was made in June 1978 but proved unsuccessful. This area was designated as a high priority area for establishment of an observation well because of the very high density of water wells throughout this area. People in this area rely entirely on the groundwater resource for their domestic water supplies. Yields have been reported as great as 454 litres/minute (100 gpm) along Dog Creek Road. The purpose of this well was to monitor groundwater extraction in the area and determine if mining of the aquifer could be taking place. Numerous wells are constructed every year along Dog Creek Road with many drilled wells supplying water to 3 or more houses. Groundwater withdrawal around the drill site is considerable. An elementary school, neighbourhood pub, 2 trailer courts and numerous houses all exist within a 300 metre radius of the observation well.

On August 1, 1980, Contract No. 70, drilling and construction of an observation well at Williams Lake was awarded to Manville Drilling of Williams Lake. Drilling was started on August 18, 1980 and completed on August 20, 1980 using an air rotary drill rig. The well is completed in fractured rock to a depth of 79.2 metres (note attached well log for complete details).

Well Location:

The well is located approximately 3.2 kilometres south of Highway 20 (Chilcotin Highway) along Dog Creek Road. The drilling site was allocated to our Section by the Ministry of Transportation and Highways in Williams Lake. The application for permission to construct works within Crown Lands has been completed and is attached to this memorandum. Mr. Jim Raven (Technician) and Mr. Stan Poloposki (District Highway Manager) assisted our staff in locating a suitable drilling site. Mr. Fred A. Baxter (Land Manager) of Ministry of Lands, Parks and Housing in Williams Lake assisted in the preliminary "footwork" involved. Mr. Zeke Withler (Regional Manager) of Fish and Wildlife was contacted and informed of the location of the observation well (Mr. Withler is responsible for the storage shed beside the well).

Monitoring Arrangement

As the application form stipulates water levels will be monitored for a minimum of 5 years.

Legal Location is:

Cariboo Land District, Plan 8645,
District Lot 9849, Lot A
Coordinates 22-X14-Y4
NTS 93-B-1

Well Drilling Specifications:

Depth	- 79.2 metres
Diameter	- 203 mm
Aquifer	- rock
Screen location	- n/a
Well yield	- *(Note pumping test discussion)
Well drilled by	- Manville Drilling
Static Water Level	- 25.49 ^m (83.64 feet) Sept. 5, 1980
Drilling method	- air rotary
Drilling time	- approx. 20 hours (Aug. 18-19th)
Drilling cost	- \$8,092.00

Pumping Test:

The pumping test was initially started on September 3rd at a pumping rate of between 191 and 205 litres/minute (42 and 45 Igpm or 54 USgpm) with a 5 hp Jacuzzi pump set at a depth of 60 metres below the top of casing. This test had to be discontinued however, after a period of 70 minutes due to a pump failure. Another pump was purchased from the Jacuzzi office in Calgary and the test was continued September 5th. This time the pump was set at 42.7 metres below the top of casing resulting in an increased pumping rate of between 248 and 273 litres/minute (54.5 and 60 Igpm or 72 USgpm). This test was continued for a period of 9.5 hours resulting in a drawdown of 0.83 metres (2.72 feet). This well had approximately 33.5 metres (110 feet) of available drawdown at the time of testing. Recharge to the well is most likely occurring from higher elevations to the south (Bond Lake, Chimney Creek regions). This theory is discussed in greater detail in the report to follow this memorandum.

Equipment on Site:

Metric Recorder - RG-46 (1:2 Gears metric)
Weight Drive Clock - CG 11
152 mm diameter threaded nipple welded to casing
Weight Drive Pipe
0.5 kg Clock Weight
340 gr. of Counterweight
1 - 127 mm diameter Float
1 - 10 metre grad. tape
21.3 metres of braided nylon line
1 - recorder stand w/GE pulley
1 - year supply of metric recorder charts (F-4) stamped "on" and "off"
2 - cable clips
1 - viro lock

The recorder was painted dark green upon completion. Reference to ground level has been shown with an arrow on the well casing.

Observer Name and Particulars:

Harris Wilkinson
134 Mayfield Avenue
Williams Lake, B.C.
392-5286
SI 705-126-258

Mr. Wilkinson was chosen as the observer because he presently services the Scout Island Observation Well (WR 85-69) and has proven to be an excellent observer.

Ground Level Datum:

Casing stick-up from tape pointer to ground level - 1.22 metres (4.00 feet)

Distance to water level from tape pointer - 25.80 metres (84.86 feet)

Tape reading - 4.106 metres

Correction factor to be applied to tape reading is therefore +20.534 metres.

References


Choy, H.H. (1978) Preliminary preposal and cost estimates for Observation Well Network Program 1978.
File 0183613-B Groundwater Section, Hydrology Division, Water Investigations Branch, Ministry of the Environment.

W.S. Hodge

W.S. Hodge, Technician
Groundwater
Hydrology Section

WSH/jm

Williams Lake Observation Well
WR-261-80 - DOG CREEK ROAD





THE GOVERNMENT OF THE PROVINCE OF BRITISH COLUMBIA

MINISTRY OF TRANSPORTATION, COMMUNICATIONS AND HIGHWAYS
(HIGHWAYS)

Application for Permission to Construct Works within Crown Lands

I (We) hereby apply for permission to construct, use, and maintain works within the limits of Crown lands under the jurisdiction of the Minister of Transportation, Communications and Highways (Highways), British Columbia, in accordance with the particulars, plans,* and specifications submitted herewith in triplicate. It is understood that the completion of this form constitutes an application only and that the works applied for will not be commenced until a covering permit has been issued. The proposed works consist of and are described as follows:

The drilling and completion of a six-inch diameter well near Williams Lake on Lot A, Plan 8645, D.L. 9849; the location of which is shown on the attached plan. After the completion of well construction, pumping test and water quality sampling, it is intended to install an automatic water level record to monitor the groundwater level for a minimum period of five (5) years. The recorder will be housed by a metal box (18" X 24" X 24") which is connected to a casing projecting approximately five feet above the ground surface. Servicing and maintenance of the recorder will be handled by Ministry of Environment staff or their representatives.

Have the necessary plans for approval been filed with the proper authorities? (See Note 2 on back)

Name of applicant: Inventory and Engineering Branch, Ministry of Environment

P.O. address: Parliament Buildings, Victoria, B.C. V8V 1X5

(Signed) _____ (Applicant.)

(Date) _____

To Local Office, Ministry of Transportation, Communications and Highways (Highways)

* See note No. 1 on back.

(OVER)

APPENDIX "B"

Water Quality Lab Reports, Schoeller Plots,
Water Level Recorder Graphs Showing Earthquake Response

SEPTEMBER 25, 1980

ENVIRONMENTAL LABORATORY
MINISTRY OF THE ENVIRONMENT

WATER QUALITY REPORT FOR SAMPLE 014539W

TO: INVENTORY & ENGIN. H.Q.
777 BROUGHTON ST., 4FLR.
VICTORIA BC

FOR SITE: 1401768 KENDALL ACRES WILLIAMS LK

SAMPLING DATE(S): AUG 25/80 1200 HRS

SAMPLE TYPE: FRESH WATER

SAMPLING DEPTH: 0

SAMPLED BY: INVENT. & ENGNRG BR., MOE

DATE RECEIVED BY LABORATORY: AUG 26/80

0040101	PH	8.3	0071701	RES:FILT.10SC	484.
		REL UNIT			MG/L
0110101	SPECIFIC CONDUCT	798.	0300101	COMP.DIL.COND.	883.
		UMHO/CM			UMHO/CM
1010101	ALKALINITY:PHNL	L 0.5	1020101	ALKALINITY:TOT	385.
		MG/L			MG/L
1041702	CHLORIDE:DISSOL	5.7*	1070002	HARDNES,T:CaCO3	218.*
		MG/L			MG/L
1091703	NITROGN:NO2 NO3	0.38	1130101	NITROGN:KJELDAH	0.10
		MG/L			MG/L
1191703	PHOSPHORUS :TOT DISSOLVED	0.058 MG/L	1190103	PHOSPHORUS :TOT	0.059 MG/L
1201702	SILICA:REACTIVE	22.4	1211701	SULPHATE:DISSOL	56.4*
		MG/L			MG/L
2541802	CALCIUM DISSOLVED	28.6* MG/L	2591801	MAGNESIUM DISSOLVED	35.5* MG/L
2641703	POTASSIUM DISSOLVED	3.8* MG/L	2651703	SODIUM DISSOLVED	107. MG/L

THE APPROXIMATE COST OF THE ABOVE TESTS IS \$ 52,60

THERE IS NO CHARGE FOR THE FOLLOWING TESTS

257U IRON

E

SAMPLE NO. 014539W CONTINUED ON NEXT PAGE.

WATER QUALITY REPORT FOR SAMPLE 015277W

TO: INVENTORY & ENGIN. H.Q.
777 BROUGHTON ST. 4FLR.
VICTORIA BC

FOR SITE: 1401769 WILLIAMS LK CONTRACT 70

SAMPLING DATE(S): SEP 8/80 1300 HRS

SAMPLE TYPE: FRESH WATER

SAMPLING DEPTH: 83

SAMPLED BY: INVENT. & ENGNRG BR., MOE

DATE RECEIVED BY LABORATORY: SEP 09/80

0040101	PH	8.0	0071701	RES:FILT,10SC	696.
		REL UNIT			MG/L
0110101	SPECIFIC CONDOC	1140.	0300101	COMP.DIL.COND.	1310.
		UMHO/CM			UMHO/CM
1010101	ALKALINITY:PHNL	L 0.5	1020101	ALKALINITY:TOT	553.
		MG/L			MG/L
1041702	CHLORIDE:DISSOL	36.9	1061701	FLUORIDE:DISSOL	0.19
		MG/L			MG/L
1070002	HARDNES.T:CaCO3	547.	1091703	NITROGN:NO2 NO3	6.6
		MG/L			MG/L
1130101	NITROGN:KJELDAH	0.57	1191703	PHOSPHORUS :TOT	0.029
		MG/L		DISSOLVED	MG/L
1201702	SILICA:REACTIVE	22.0	1211701	SULPHATE:DISSOL	30.2
		MG/L			MG/L
2541413	CALCIUM	66.4	2570209	IRON	1.3
	DISSOLVED	MG/L		TOTAL	MG/L
2571413	IRON	1.21	2591413	MAGNESIUM	92.7
	DISSOLVED	MG/L		DISSOLVED	MG/L
2600209	MANGANESE	0.04	2601401	MANGANESE	0.03
	TOTAL	MG/L		DISSOLVED	MG/L
2641703	POTASSIUM	7.2	2651703	SODIUM	38.6
	DISSOLVED	MG/L		DISSOLVED	MG/L

THE APPROXIMATE COST OF THE ABOVE TESTS IS \$ 65.90

SAMPLE NO. 015277W CONTINUED ON NEXT PAGE.

WATER QUALITY REPORT FOR SAMPLE 015278W

TO: INVENTORY & ENGIN. BR.
777 BROUGHTON ST.
VICTORIA, B.C.

FOR SITE: 1401769 WILLIAMS LK - CONTRACT 70

SAMPLING DATE(S): SEP 8/80 2000 HRS

SAMPLE TYPE: FRESH WATER

SAMPLING DEPTH: 83


SAMPLED BY: INVENT. & ENGNRG BR., MOE

DATE RECEIVED BY LABORATORY: SEP 09/80

0040101	PH	8.0	0071701	RES:FILT,10SC	700.
		REL UNIT			MG/L
0110101	SPECIFIC CONDUCT	1140.	0300101	COMP.DIL.COND.	1310.
		UMHO/CM			UMHO/CM
1010101	ALKALINITY:PHNL	L 0.5	1020101	ALKALINITY:TOT	553.
		MG/L			MG/L
1041702	CHLORIDE:DISSOL	35.5	1061701	FLUORIDE:DISSOL	0.20
		MG/L			MG/L
1070002	HARDNES.T:CaCO3	567.*	1091703	NITROGN:NO2 NO3	6.70
		MG/L			MG/L
1130101	NITROGN:KJELDAH	0.58	1191703	PHOSPHORUS :TOT	0.066
		MG/L		DISSOLVED	MG/L
1201702	SILICA:REACTIVE	22.6	1211701	SULPHATE:DISSOL	29.7
		MG/L			MG/L
2541802	CALCIUM	68.8*	2570209	IRON	0.1
	DISSOLVED	MG/L		TOTAL	MG/L
2571413	IRON	0.1	2591801	MAGNESIUM	96.*
	DISSOLVED	MG/L		DISSOLVED	MG/L
2600209	MANGANESE	0.02	2601401	MANGANESE	L 0.02
	TOTAL	MG/L		DISSOLVED	MG/L
2641703	POTASSIUM	7.3	2651703	SODIUM	37.9
	DISSOLVED	MG/L		DISSOLVED	MG/L

THE APPROXIMATE COST OF THE ABOVE TESTS IS \$ 65.90

Schoeller Plot



TO ACCOMPANY REPORT ON

Construction of Observation Well
WR 261-80 Williams Lake Area

D.A. Lowen ENGINEER

FILE No. _____ DWG. No. Appendix B

Water Investigations Branch
Ministry of the Environment
Parliament Buildings
Victoria, B.C.
V8V 1X9

STN. NAME Williams Lake

NO. 209

ON

DATE Dec 1/80

TIME 235

LEVEL 4.046 m

OFF

DATE Dec 31/80

TIME 430

LEVEL 4.013

(6'-6" dia)

EARTHQUAKE DEC 17th 9:20 P.M.
~200 Km WEST OF ESTERAN Pt. ON VANCOUVER
ISLAND

24.580

8012010935

24.527

8012311630

#261

AA401769

2:1



Province of British Columbia
Ministry of Environment
INVENTORY AND ENGINEERING BRANCH

TO ACCOMPANY REPORT ON

Construction of Observation Well
WR 261-80 Williams Lake Area

SCALE: VERT.

HOR.

DATE

October 1980

D.A. Lowen

ENGINEER

FILE No

DWG No

Appendix B

Ministry of the Environment
Parliament Buildings
Victoria, B.C.
V8V 1X5

STN. NAME WR 261-80 NO. 261-80

ON

DATE Nov 1 1980 TIME 2:20 LEVEL 3.983

OFF

DATE Dec 1 1980 TIME 9:35 LEVEL 4.046

*Southern Italy
EARTHQUAKE Nov 8, 1980*

24.517
8011011420

24.580
8012010935

#261
AA-401769
2-1



Province of British Columbia
Ministry of Environment
INVENTORY AND ENGINEERING BRANCH

TO ACCOMPANY REPORT ON

Construction of Observation Well
WR 261-80 Williams Lake Area

SCALE: VERT.

HOR.

DATE

October 1980

D.A. Lowen

ENGINEER

FILE No

DWG No

Appendix B